2505 Horse Pasture RD, Suite 105 Virginia Beach, VA 23453 Phone (757) 426-7686 Fax (757) 453-6500

Your Total RF Solution



UHF 200 Watt SATCOM Diplexer / Combiner PT # RF-TSD-243-318 V3





- •Allows simultaneous use of two UHF SATCOM Transceivers (200 Watts per channel) with one antenna. Built in 27 dB Low Noise Amplifier (LNA) per channel
- •No TX/RX switching, isolation between TX & RX bands takes place through custom filters ensuring compatibility with all of the fast switching communication modes
- •Standard model, Size: 8.35" W x 15.4"L x 5.25"H, Weight: 18.75 lbs
- •Custom Waterproof Enclosure w/ (3) N-type RF Female Connections, (1) MS-3112E8-2P Power Connector and (1) 3-position Power Switch w/ LED Power Indicator
- •Frequency Range 243-270 MHz Receive, 292-318 MHz Transmit
- •Three modes of operation: 1. Off; 2. Radio One Only (bypass the combiner and the LNA is on; 3. Radio One and Two (normal two radio operation).
- •Ability to power the unit through local power connection or through the Radio 1 RF Connector via a Bias "T" circuit (9-28 VDC input)
- •Great for use on Maritime Craft, Vehicles, Base Stations and other platforms that are limited for antenna space